

Working with Files: Takeaways

by Dataquest Labs, Inc. - All rights reserved © 2021

Syntax

- Create a file

```
touch [name of file]
```

- Print text

```
echo [string of text]
```

- Write text to file

```
echo [string of text] > [name of file]
```

- Edit a file without redirection

```
nano [name of file]
```

- View permissions on files and folders

```
ls -l
```

- Get info about a file

```
stat [file name]
```

- Modify file permissions

```
chmod [octal notation integer] [file name]
```

- Move file

```
mv [file name] [destination path]
```

- Copy file

```
cp [file name] [new file name]
```

- Delete file

```
rm [name of file]
```

- Switch and run as root user

```
sudo
```

Concepts

- Every program writes to standard output and receives input through standard output.
- If the program throws an error while running, it writes it to standard error.
- `stderr` and `stdout` usually display on the monitor, while `stdin` is the input from the keyboard.
- `stdout`, `stderr`, and `stdin` exist because these standard streams allow the interfaces to be abstract.
- We can redirect standard streams to connect them to different sources.

- In Unix, every file and folder has permissions associated with it. These permissions have three scopes:
 - **owner** : The user who created the file or folder
 - **group** : Users in the owner's group (on Unix systems, an owner can place users in groups)
 - **everyone** : All other users on the system who aren't the user or in the user's group
- Each scope can have any of three permissions (a scope can have multiple permissions at once):
 - **read** : The ability to see what's in a file (if defined on a folder, the ability to see what files are in a folder)
 - **write** : The ability to modify a file (if a folder, the ability to delete, modify, and rename files in the folder)
 - **execute** : The ability to run a file (some files are executable, and need this permission to run)
- Each permission can be granted or denied to each scope.
- The character for read is **r**, the character for write is **w**, and the character for execute is **x**.
- If a scope doesn't have a permission, a dash takes the place of it instead.
- We can use octal notation to represent permissions for all scopes with 4 digits.
 - **---** : No permissions; corresponds to 0
 - **--x** : Execute only permission; corresponds to 1
 - **-w-** : Write only permissions; corresponds to 2
 - **-wx** : Write and execute permissions; corresponds to 3
 - **r--** : Read only permissions; corresponds to 4
 - **r-x** : Read and execute permissions; corresponds to 5
 - **rw-** : Read and write permissions; corresponds to 6
 - **rwX** : Read, write, and execute permissions; corresponds to 7
- Files typically have extensions like .txt and .csv that indicate the file type.
- Rather than relying on extensions to determine file type, Unix-based operating systems like Linux use media types, which are also called MIME types.
- The root user has all permissions and access to all files by default.

Resources

- [Standard streams](#)
- [Octal](#)